



Dispensette® III, Digital Easy Calibration Bottletop Dispenser

Dispenser Dispensette® III Digital EasyCal., 2,5-25ml, with SafetyPrime

Packaging: 1 piece

Cat. No.: 4700351

389,00 EUR

Recommended sales price without VAT (PL 2013)
per 1 on orders of 1.

Product description

The wide range of Dispensette® dispensers provides premium dispensing options for the complete spectrum of liquid reagents. **Dispensette® III (red color-code)**: For dispensing aggressive reagents, including concentrated acids such as H₃PO₄, H₂SO₄, bases like NaOH, KOH, saline solutions, as well as many organic solvents - directly from the supply bottle. **Features at a glance:**

- Digital display: especially easy to read, and dispensing volume can be set accurately and reproducibly (mechanical counter). Easy Calibration: Innovative technique for adjustment in seconds without tools.

Alteration of factory setting is automatically indicated by a red recalibration flag.

- The Dispensette® is easy for dismantle for cleaning, has replaceable filling valves and is autoclavable at 121 °C.

- The parts of the Dispensette® III which are in contact with medium consists of the following high-grade materials: borosilicate glass, ceramic, platinum-iridium, ETFE, FEP and PFA. The discharge tube safety screw cap is PP.

- Operating limits: vapor pressure max. 500 mbar, viscosity max. 500 mm²/s, temperature max. 40 °C, density max. 2.2 g/cm³.

Items supplied

Each Dispensette® is conformity certified and supplied with performance certificate, discharge tube, telescoping filling tube, SafetyPrime(TM) recirculation valve (optional), mounting tool and adapters of polypropylene .

Specification

Capacity	ml	2,5 - 25
subdivision	ml	0,1
A	≤ ± %	0,5
A	≤ ± µl	125
CV	≤ %	0,1
CV	≤ µl	25
SafetyPrime		with